

Model: 4IBC



Storage:	4x1000L IBC's stored on 2 levels.
Overall dimensions:	3100L x 1500W x 3100H - mm
Construction:	Robust all welded 100x50mm steel box section frame.
Sumps:	Corrosion resistant coated steel sump tray fitted under lower shelf level. Total Capacity: 1100L (exceeds current EPA guidelines , 25% of the total volume).
Shelving:	Shelving constructed from galvanised grid decking, supported by 50x50mm box section steel, fully welded.
Access:	Twin, heavy-duty sliding access doors, fully padlockable .
Wall/Roof/Door Cladding:	2mm profiled steel vandal proof cladding.
Finish:	All steel coated with high specification 2-pack, chemical resistant, polyurethane finish system, designed for aggressive environments. Choice of colours. Std colour: Blue RAL 5017.
Lifting:	Unit is fitted with forklift channels to allow for easy unloading and relocation if required.
Signage:	Relevant safety signs fitted as standard on all units. Specific signage available on request.

Unloading is the responsibility of the client company, arrangements may be required depending on the site and unit supplied.

External 8 IBC Store



Storage:	8 x 1000litre IBC's on 2 levels.
Overall dimensions:	5.9m L x 1.5m W x 3.1m H
Floor Loadings:	3000kgs
Door Openings:	2600mm
Shelving Height:	1250mm
Construction:	Vandal proof all welded 2mm steel throughout. Fully padlockable. Floor contact points are fully galvanised then painted. Fully welded steel panels create a fully vandal proof secure construction.
Sumps:	Sump Capacity: 2100litres Bundling under floor level is leak tested and certified. Steel bund is suitable for flammable liquids and most chemicals. Grid mesh decking on floor for small/loose container storage.
Ventilation:	Side air vents for good natural airflow throughout.
Finish:	Industrial 2 pack epoxy paint finish is highly chemical resistant. Choice of 3 colours – Blue RAL 5017, Green RAL 6003, Red RAL 3020.
Lifting:	Forkliftable and also fitted with lifting lugs enabling the unit to be moved with a crane for unloading and relocation if required. Weight: 2200kgs
Signage:	Relevant safety signs fitted as standard on all units. Specific signage available on request.

Unloading is the responsibility of the client company, arrangements may be required depending on the site and unit supplied.

Model: 12 IBC-Store



- Storage:** 12 pallets (48 no. of 200L drums) stored on two levels, in six columns. Similar to picture
- Overall dimensions:** 8800L x 1500W x 3100H mm
- Construction:** Robust all welded 100x50mm heavy-duty steel box section. 2mm steel profiled vandal proof sheets fitted to walls, roof & doors
- Sumps:** Corrosion resistant leak tested and certified steel sump trays under floor level, capacity 3600L (**easily exceeds EPA guidelines – 25% of the total likely to be stored**).
- Shelving:** Shelving constructed from galvanised grid decking.
- Access:** Twin sliding doors on Henderson heavy duty slide mechanism. Doors provide access to 6 pallets at any one time. **All doors fully lockable.**
- Lifting:** Unit is fitted with forklift channels and roof-fixed crane lifting points to allow for easy unloading/relocation.
- Ventilation:** Fully weather-proof, louvred panels are used to ensure good airflow throughout the store.
- Finish:** All steel coated with 2 pack anti corrosive polyurethane paint system. Choice of colours. Standard colour: Blue RAL 5017.
- Signage:** Relevant signage fitted as standard
- Delivery:** **3-4 Weeks from receipt of order.**